

OPTOTRONIC FIT D NFC L

Linear / Área Corrente Constante – Não regulável



Áreas de aplicação

- Instalação em sistemas de iluminação de emergência conforme IEC 61347-2-13, anexo J
- Indicado para instalação em sistemas de iluminação de emergência conforme EN 60598-2-22
- Adequado para luminárias de classe de proteção I

Características do produto

- Frequência da linha: 0 Hz | 50 Hz | 60 Hz
- Tensão de alimentação: 220...240 V

Ficha técnica da família de produto

Informações sobre aplicações

Para obter mais informações sobre aplicações e gráficos acesse a ficha técnica do produto.

Vendas e suporte técnico

Vendas e suporte técnico www.osram.br

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Retrato

Sujeito a alterações sem prévio aviso. Sempre utilize a versão mais recente.