

LF500 -G1-930-10 L2

LINEARlight FLEX Low Power IP00 | Módulos LED para aplicações profissionais e industriais



Dados técnicos

Dados elétricos

Tensão nominal	240 V
Tipo de corrente	Corrente contínua (DC)
Potência nominal por metro	3,9 W
potência nominal	3900 W
Gama de tensão de entrada	23...25 V
Accidental reverse input voltage protection up to	25 V

Dados fotométricos

Cor da luz do LED	branco
Índice de reprodução de cor Ra	≥90
Fluxo luminoso por metro	400 lm
Fluxo luminoso útil total	4000 lm
Rendimento luminoso	103 lm/W
Desvio padrão de combinação de cores	≤3 sdc _m
Tonalidade (designação)	3000 K
Temperatura de cor	3065 K
Temperatura de cor	3065 K

Dados luminotécnicos

LED pitch	14.29 mm
Ângulo de abertura	120 °
Tempo de ligamento	< 05 s
Tempo de aquecimento (60 %)	< 050 s

Informação sobre módulos LED

Número de LEDs por metro	70
Número de LEDs por menor unidade	7

Dimensões e peso



Comprimento	100000 mm
Comprimento da menor unidade	100,0 mm
Peso do produto	8640 g
Secção do cabo, primário	0.51 mm ²
Largura	800 mm
Altura	140 mm

Temperaturas e condições de funcionamento

Temp. funcionamento, conforme IEC 62717	35 °C
Gama de temperatura no funcionamento	-30...75 °C ¹⁾
Temperatura de armazenagem	-40...85 °C

¹⁾ Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.

Vida útil

Vida	60000 h
Vida nominal	60000 h
Número de ciclos de Liga e Desliga	15000

Informação adicional do produto

ID of contained light source [AGGR]	LS_TRV_274094
-------------------------------------	---------------

Atributos

Lowest bending radius	20 mm
Self-adhesive	Sim
With connection set	Não
With end piece	Não

Normas e Certificações

Consumo de energia	43 kWh/1000h
Normas	CE/UL/ENEC/EAC
Tipo de protecção	IP20
Energy efficiency class of the contained light source	F

Dados logísticos

Código do material	85395100000
--------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-07-2023
Primary Article Identifier	4062172272094
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	93857245-ef62-45c2-a563-ad6defb8cb90

Texto ficha técnica

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Download Data

Arquivo	
	User instruction LINEARlight FLEX Low Power
	Product Datasheet LINEARlight FLEX Low Power LF500 L2 Specification Sheet (EN)
	Brochures Light is freedom of design (EN)
	Certificates VDE-ENEC Certificate
	Declarations of conformity LF500-G1 CE 3657641 221121

Ficha técnica do produto

	Declarations of conformity Manufacturers Declaration of Conformity 3657643
	Eulumdat Eulumdat LF500-G1-930-10
	IES data IES data LF500-G1-930-10

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dados de Logística

Código do produto	Descrição do produto	Embalagem unitária (peças/unidade)	Dimensões (comprimento x largura x altura)	Volume	Peso bruto
4062172272094	LF500 -G1-930-10 L2	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm³	1624.00 g

O código do produto mencionado indica a quantidade mínima a ser adquirida. Uma caixa unitária pode conter um ou mais produtos. Quando for colocar o pedido de compras, indique uma quantidade unitária ou múltiplos da caixa unitária.

acessório opcional

Descrição do produto	nome do acessório	código do acessório
LF500 -G1-930-10 L2	CONN-FLEX -2P-050 KIT 10PCS	▶ 4062172179591
LF500 -G1-930-10 L2	CONN-FLEX -2P-200 KIT 10PCS	▶ 4062172179614
LF500 -G1-930-10 L2	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638

Ficha técnica do produto

LF500 -G1-930-10 L2	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
LF500 -G1-930-10 L2	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
LF500 -G1-930-10 L2	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LF500 -G1-930-10 L2	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LF500 -G1-930-10 L2	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
LF500 -G1-930-10 L2	FX -SC08-G2-CT4PJ	▶ 4052899464858

Retrata o

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.