

BA-RGBW-PL G2

BackLED RGBW Plus G2 | Módulos LED para publicidade e retroiluminação



Características do produto

- Conectado com cabos flexíveis
- Encapsulamento resistente especial
- Marcação CE
- Dimerizável por modulação de largura de pulso (PWM)

Benefícios do produto

- Fixação simples com parafusos M3
- Paleta de mistura de cores ampla (em conexão com os sistemas de gerenciamento de luz)
- Backlighting uniforme de superfícies grandes graças aos elementos ópticos de ângulos extremamente grandes
- Conexão simples com extremidades de cabos abertas
- 5 anos de garantia



Áreas de aplicação

- Special-purpose and decorative lighting applications
- Backlighting com cor dinâmica
- Controle de iluminação dinâmica
- Spas
- Lojas
- Restaurantes
- Iluminação de feiras de negócios
- Uso externo permanente em caixas de luz embutidas ou letreiros de perfis

Dados técnicos

Dados elétricos

Tensão nominal	24,0 V
Potência nominal por módulo LED	2,84 W
Accidental reverse input voltage protection up to	24 V
Gama de tensão de entrada	23...25 V
Tipo de corrente	Corrente contínua (DC)
Potência nominal por cadeia	42,60 W


Dados fotométricos

Tonalidade (designação)	RGBW
Cor da luz do LED	RGB, 6500 K
Fluxo luminoso por cadeia de módulo	2310 lm
Rendimento luminoso	54 lm/W
Desvio padrão de combinação de cores	≤5 sdc _m
Fluxo luminoso por módulo LED	154 lm
Luminous flux per LED module at Ta 25 °C	142 lm
Luminous flux per LED module at Tc 25 °C	154 lm
Luminous flux per chain at Ta 25 °C	2125 lm
Luminous flux per chain at Tc 25 °C	2310 lm

Informação sobre módulos LED

Número de LEDs por módulo	8
Número de módulos LED por cadeia	15
Núm. mín. de módulos LED.	3

Dimensões e peso



Peso do produto	900,00 g
-----------------	----------

Ficha técnica do produto

Comprimento	6400,0 mm
Largura	35,0 mm
Altura	15,50 mm
Module length	70.5 mm
Module pitch	500 mm

Temperaturas e condições de funcionamento

Gama de temperatura no funcionamento	-25...75 °C
Temperatura de armazenagem	-25...65 °C

Informação adicional do produto

ID of contained light source [AGGR]	LS_SHZ_600870
EAN sucessor	4052899452930

Atributos

Faixa de dimerização	5...100 %
----------------------	-----------

Normas e Certificações

Tipo de protecção	IP66
Normas	CE
Selo de aprovação	CE
Energy efficiency class of the contained light source	G

Dados logísticos

Código do material	85395100000
--------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	16-06-2023
Primary Article Identifier	4062172030168
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained



484525_5 Year Osram Guarante
(GB)

Equipamento / Acessórios

- Vários tipos de fontes de alimentação disponíveis OPTOTRONIC 24 V
- Perfis de montagem BoxLED

Texto ficha técnica

- Installation of LED modules (with power supplies) needs to be made under consideration of all valid regulations and norms.
- Installation by qualified electrician only.
- Please see the relevant application guides and instructions sheets for more detailed safety and mounting information. Additional information is available on request.
- Complies with IEC/EN 61547
- Complies with IEC/EN 61000-3-2
- Complies with EN 55015, CISPR 15
- Complies with IEC/EN 61347-1
- Complies with IEC/EN 61347-2-13
- LED modules are dimmable by means of PWM (pulse width modulation). It is recommended using the following OSRAM control gears: OPTOTRONIC OT DIM or OPTOTRONIC 24 V power supplies with integrated 1...10 V dimming interface.
- Parallel connection is mandatory for safe electrical operation. Serial connection of LED modules is strongly discouraged. Unbalanced voltage drop in serial connection can cause hazardous overload and damage the LED module.
- Electrical contact is achieved with the contact cables or the terminals of the module. Please refer to the technical data for maximum number of LED modules that can be operated on one control gear.
- In order to operate OSRAM LED modules safely, it is absolutely necessary to operate them with an electronically stabilized power supply that protects against short circuits, overload and overheating.
- In case other power supplies than OSRAM OPTOTRONIC are used, compliance to the necessary operating parameters (voltage, current, power) has to be ensured.
- Pay attention to polarity! Wrong polarity can cause destruction or malfunction of the module.
- Conducting paths on the circuit board must not be damaged or destroyed during installation.
- The LED module itself and all its components must not be stressed mechanically.
- Operation in or under water is prohibited.
- To avoid mechanical damage, the LED modules have to be attached securely to the intended mounting surface. It is recommended to avoid heavy vibration.
- In case that the LED module is equipped with a pre-mounted double-sided adhesive tape, OSRAM assumes no liability and provides no guarantee for a permanent adherence of the modules to the surface. OSRAM recommends fixation of the modules by means of suitable screws.
- Complies with IEC 61347-1 cl. 18.3, cl. 18.4, IEC 60695-2-10, IEC 60695-11-5, IEC 60695-11-10 (classification V-0)
- All the technical parameters apply to the entire module. In view of the complex manufacturing process for light emitting diodes, the specified typical values for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values.
- Module contains no PVC material.
- To ensure uniform illumination, a reflective matt white surface is generally recommended for all internal frame walls and back panels of light boxes.
- The module may cause noises during dimming. If a dimming operation is required, it is recommended to check the dimming operation for noises before final installation.

Download Data

Arquivo	
	User instruction UI BackLED TW and RGBW Plus G2
	Brochures Technical application guide BackLED and BoxLED portfolio (EN)
	Declarations of conformity BACKLED PLUS G15 CE 3320783 06 260723

Ficha técnica do produto

	Declarations of conformity 727532_Manufacturer's Declaration BackLED PLUS
	CAD data 728616_CAD_BackLED RGBW Plus G2_dwg
	CAD data 728617_CAD_BackLED RGBW Plus G2_isg
	CAD data 3-dim 728618_CAD_BackLED RGBW Plus G2_step
	CAD data PDF 728615_CAD BackLED RGBW Plus G2_pdf
	Eulumdat 728621_BackLED RBGW Plus G2 BA-RGBW-PL_Blue_4052899452930
	Eulumdat 728622_BackLED RBGW Plus G2 BA-RGBW-PL_Green_4052899452930
	Eulumdat 728623_BackLED RBGW Plus G2 BA-RGBW-PL_RGBW_4052899452930
	Eulumdat 728624_BackLED RBGW Plus G2 BA-RGBW-PL_Red_4052899452930
	Eulumdat 728625_BackLED RBGW Plus G2 BA-RGBW-PL_White_4052899452930
	IES data IES_BackLED RBGW Plus G2
	IES data IES_BackLED RBGW Plus G2
	IES data IES_BackLED RBGW Plus G2
	IES data IES_BackLED RBGW Plus G2
	IES data IES_BackLED RBGW Plus G2

Ficha técnica do produto

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dados de Logística

Código do produto	Descrição do produto	Embalagem unitária (peças/unidade)	Dimensões (comprimento x largura x altura)	Volume	Peso bruto
4062172030168	BA-RGBW-PL G2	Shipping carton box 5	473 mm x 328 mm x 292 mm	45.30 dm³	7277.00 g

O código do produto mencionado indica a quantidade mínima a ser adquirida. Uma caixa unitária pode conter um ou mais produtos. Quando for colocar o pedido de compras, indique uma quantidade unitária ou múltiplos da caixa unitária.

Referências / Links

For more information on the multi-level guarantee and the terms and conditions of the guarantee visit <https://www.inventronics-light.com/multilevel-guarantees>

Retrato

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.