

BackLED Area White

Módulos LED para publicidade e retroiluminação



Características do produto

- Módulos LED 24 V corrente constante
- Temperatura da cor: 2.700 K, 3.000 K ou 4.000 K
- Índice de reprodução de cor R_a: > 90
- Distância constante dos LEDs mesmo nas interligações da placa
- Cuttable, single board for an exact fit in any installation

Benefícios do produto

- Proporciona luz homogénea para aplicação em luminárias para iluminação de grandes áreas
- Easy wiring with push-in connectors
- Baixo consumo de energia e menos geração de calor
- Optimal operation on OPTOTRONIC 24VDC and 24VDC dimmable power supplies

Áreas de aplicação

- Iluminação de área
- Tetos de luz
- Hospitalidade, hotéis, restaurantes
- Museus, galerias de arte
- Backlighting shallow box signs

Ficha tocnica da famolia de produto

Informa � � es sobre aplica � � es

Para obter mais informa ��es sobre aplica ��es e gr�ficos acesse a ficha t�cnica do produto.

Vendas e suporte t�cnico

Vendas e suporte tocnico www.osram.br

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Retrata � � o

Sujeito a altera��o sem pr�vio aviso. Sempre utilize a vers�o mais recente.