

# **ICUTRONICS FIT CS Track**

# Constant Current Compact - Non dimmable



#### Características do produto

- AC Supply Voltage 220-240 Vac
- Frequência da linha: 50 Hz | 60 Hz
- Tensão da linha: 198...264 V
- SELV LED driver in track adaptor
- Lifetime 50 000 h at tc max
- Dip-switches for easy output current selection
- Low THD <10% @ full load
- Low LF-ripple < 5%

## Benefícios do produto

- Compact size for miniaturized track light luminaire design
- High light quality due to low ripple current
- Three colors available: White, Grey, Black

### Areas de aplicação

- Shops
- Lojas de varejo
- Prédios públicos
- Adequado para luminárias de classe de proteção II
- Suitable for three circuits system

# Ficha tocnica da famolia de produto

### Informa � � es sobre aplica � � es

Para obter mais informa ��es sobre aplica ��es e gr�ficos acesse a ficha t�cnica do produto.

#### Texto ficha técnica

- Hot plug-in or secondary switching of LEDs is not permitted and may cause a very high current to the LEDs.
- Indication that the lamp control gear relies upon the luminaire enclosure for protection against accidental contact with live parts.
- The max. mechanical loading Fmax for the track driver mounted on the ceiling is 50N, which shouldbe intended as the whole system inclusive of the weight of luminaires and accessories.
- The max. mechanical loading Fmax for the track driver mounted on the wall is 25N, which should be intended as the whole system inclusive of the weight of luminaires and accessories.

#### Vendas e suporte t�cnico

Vendas e suporte t�cnico www.osram.br

#### Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

#### Retrata � � o

Sujeito a altera ��o sem pr�vio aviso. Sempre utilize a vers�o mais recente.