

## LEDDriving SL W16W RED

Ideal replacement for any vehicle



**Suitable for various vehicle exterior applications**

Available in Red




**Replaces conventional W16W lamps**

Easy upgrade to LED technology with plug & play solutions



**Reliable OSRAM quality stands for less lamp replacements**

4-year OSRAM guarantee (refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions)



### Suitable LED replacement for W16W

LEDDriving SL W16W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional W16W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description           | Electrical Data |                 |                 |  | Photometric Data      |
|-------------------------------|-----------------|-----------------|-----------------|--|-----------------------|
|                               | Power input     | Nominal voltage | Nominal wattage |  | Nominal luminous flux |
| LEDiving SL $\triangleq$ W16W | 2 W             | 12 V            | 2 W             |  | 80 lm                 |

| Product description           | Luminous flux tolerance | Physical Attributes & Dimensions | Lifetime Data |             | Environmental & Regulatory Information<br>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |
|-------------------------------|-------------------------|----------------------------------|---------------|-------------|-----------------------------------------------------------------------------------------------------------------|
|                               |                         | Diameter                         | Lifespan B3   | Lifespan Tc | Primary article identifier                                                                                      |
| LEDiving SL $\triangleq$ W16W | $\pm 25\%$              | 11.0 mm                          | 1500 hr       | 4000 hr     | 4062172401630   4062172160155                                                                                   |

| Product description           | Candidate list substance 1 | CAS No. of substance 1 | Safe use instruction                                                                               | Declaration no. in SCIP database     |
|-------------------------------|----------------------------|------------------------|----------------------------------------------------------------------------------------------------|--------------------------------------|
| LEDiving SL $\triangleq$ W16W | Lead                       | 7439-92-1              | The identification of the Candidate List substance is sufficient to allow safe use of the article. | b659ede8-1f72-472c-a2de-985236aa808b |

Download Data

| File                                                                              |                                                           |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------|
|  | User instruction<br>GPRS_Safety symbols instructions      |
|  | Brochures<br>LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.