

## TYREseal KIT



### TPMS suitable

Suitable for cars with tire pressure monitoring systems



### No tools required

No need to remove the valve core  
No need for a jack



### Quick seal

Complete the sealing of your tyre within 10 minutes



### Made to OE specification

Replacement for the manufacturer's original tire sealant



### OSRAM TYREseal KIT

The OSRAM TYREseal KIT contains a 450 ml bottle of tyre sealant, a tyre compressor and a storage bag and can be used as a replacement for the manufacturer's original tyre sealant kit. The OSRAM TYREseal KIT enables you to seal tyre punctures up to 6 mm\* using the latest particle gel technology and to inflate your tyre with the tyre compressor supplied. After sealing your tyre with the OSRAM TYREseal KIT, you can continue your journey up to a distance of 200 km to get a replacement tyre from a garage or tyre dealer or, as the tyre sealant can be rinsed out again, to have the tyre permanently repaired instead of buying a new one, thus saving costs. Sealing a damaged tyre can be done quickly and easily, without tools or jacks, so you can resume your journey within 10 minutes.

Compared to foam sealants, OSRAM's sealant formula is

designed to be compatible with the vehicle's tyre pressure monitoring system (TPMS). Thanks to the valve passage technology, the valve insert does not have to be removed when using the sealant.

The OSRAM TYREseal KIT is supplied with a storage bag with Velcro fastener so that it can be stored neatly in the boot or the recess provided for this purpose in the vehicle. The OSRAM TYREseal 450 can be used as a replacement for the manufacturer's original tyre sealant. As most tyre sealants have to be replaced every 5 years, including those supplied ex works in the car, the OSRAM TYREseal 450 replacement bottle is an ideal way to replace the tyre sealant in the car after the expiry date and, in the event of a tyre puncture, to seal it and continue driving.

The OSRAM TYREseal 450 is a tyre sealant from OSRAM that uses particle gel technology to seal tyre punctures and is produced according to the OE standard of car manufacturers. Available as a set, i.e. as OSRAM TYREseal KIT with sealant, tyre compressor and storage bag or as OSRAM TYREseal 450, i.e. as a tyre sealant replacement bottle.

\*The tyre sealant cannot be used to repair damage to the sidewall of a tyre

Product family datasheet

Technical data

| Environmental & Regulatory Information<br>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                               |                           |                                                                                                                   |                                              |
|-----------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------|-------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| Product description                                                                                             | Candidate list<br>substance 1 | CAS No. of substance<br>1 | Safe use instruction                                                                                              | Declaration no. in<br>SCIP database          |
| TYRE seal KIT                                                                                                   | Lead                          | 7439-92-1                 | The identification of<br>the Candidate List<br>substance is<br>sufficient to allow<br>safe use of the<br>article. | 653c7667-ef92-<br>4a62-b24a-<br>2f38302a9fca |

Download Data

| File                                                                              |                                  |
|-----------------------------------------------------------------------------------|----------------------------------|
|  | User instruction<br>TYREseal Kit |

Safety advice

Product won't exceed noise levels of more than 90 dB

Legal advice

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.CE and EAC certified

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.