

LF1200 -G3-830-09 L2

LINEARlight FLEX High Power IP00 | Módulos LED para aplicações profissionais e industriais



Características do produto

- Fita de LED flexível e cortável

Benefícios do produto

- Color uniformity better than 2 SDCM on the entire LED strip and between strips
- Grande variedade de cores de luz
- Fácil montagem em muitas superfícies lisas devido à fita autocolante na parte de trás

Áreas de aplicação

- Iluminação com sancas
- Integração do teto



Dados técnicos

Dados elétricos

Tensão nominal	240 V
Tipo de corrente	Corrente contínua (DC)
Potência nominal por metro	8,9 W
potência nominal	8010 W
Gama de tensão de entrada	23...25 V
Accidental reverse input voltage protection up to	25 V

Dados fotométricos

Cor da luz do LED	branco
Índice de reprodução de cor Ra	>80
Fluxo luminoso por metro	1200 lm
Rendimento luminoso	135 lm/W
Tonalidade (designação)	3000 K
Temperatura de cor	3000 K



Dados luminotécnicos

LED pitch	14.29 mm
Ângulo de abertura	120 °

Informação sobre módulos LED

Número de LEDs por metro	70
Número de LEDs por menor unidade	7

Dimensões e peso



Comprimento	90000 mm
Comprimento da menor unidade	100,0 mm

Ficha técnica do produto

Comprimento do cabo	5000
Peso do produto	13100 g
Secção do cabo, primário	0.51 mm ²
Largura	800 mm
Altura	140 mm

Temperaturas e condições de funcionamento

Temp. funcionamento, conforme IEC 62717	40 °C
Gama de temperatura no funcionamento	-20...90 °C ¹⁾
Temperatura ambiente	-20...+50 °C ²⁾
Temperatura de armazenagem	-40...80 °C

1) Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.
2) Rated ambient temp. 25°C/Providing that temperature at Tc point is below max value during operation/Temperature ramping for environmental testing acc. to IEC 62717, 1K/min

Vida útil

Vida	60000 h
Vida nominal	60000 h

Informação adicional do produto

EAN sucessor	4052899953086
ID of contained light source [AGGR]	LS_TRV_216342

Atributos

Lowest bending radius	20 mm
Self-adhesive	Sim
With connection set	Não
With end piece	Não

Normas e Certificações

Normas	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
Tipo de protecção	IP00
Energy efficiency class of the contained light source	E

Dados logísticos

Código do material	85395100000
--------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-07-2023
Primary Article Identifier	4062172142618
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	bf917dd0-ee4a-493b-beea-282eb1f56af1

Equipamento / Acessórios

- Ligação simplificada compatível com acessório opcional CONNECTsystem
- Instalação rápida com SLIM TRACK System otimizado
- Combinação perfeito com reatores OPTOTRONIC de 24 V

Texto ficha técnica

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Download Data

Arquivo	
	User instruction LINEARlight FLEX POWER
	Product Datasheet LINEARlight Flex Power Specification Sheet
	Brochures Light is freedom of design (EN)
	Certificates EAC Certificate
	Certificates UL Certificate
	Certificates ENEC10_VDE Certificate
	Certificates CB TEST CERTIFICATE DE1-57844
	Declarations of conformity LF HP G3 CE 4160937 280623
	Declarations of conformity LF HP G3 CE 3420012 03 071119

Ficha técnica do produto

	Declarations of conformity EU Declaration of conformity
	Declarations of conformity Manufacturer declaration
	Eulumdat LF1200-G3-830-09 L2 LDT 28032022
	IES data LF1200-G3-830-09 L2 IES 28032022

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dados de Logística

Código do produto	Descrição do produto	Embalagem unitária (peças/unidade)	Dimensões (comprimento x largura x altura)	Volume	Peso bruto
4062172142618	LF1200 -G3-830-09 L2	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm³	1981.00 g

O código do produto mencionado indica a quantidade mínima a ser adquirida. Uma caixa unitária pode conter um ou mais produtos. Quando for colocar o pedido de compras, indique uma quantidade unitária ou múltiplos da caixa unitária.

acessório opcional

Descrição do produto	nome do acessório	código do acessório
LF1200 -G3-830-09 L2	CONN-FLEX -2P-050 KIT 10PCS	▶ 4062172179591

Ficha técnica do produto

LF1200 -G3-830-09 L2	CONN-FLEX -2P-200 KIT 10PCS	▶ 4062172179614
LF1200 -G3-830-09 L2	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638
LF1200 -G3-830-09 L2	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
LF1200 -G3-830-09 L2	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
LF1200 -G3-830-09 L2	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LF1200 -G3-830-09 L2	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LF1200 -G3-830-09 L2	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
LF1200 -G3-830-09 L2	FX -SC08-G2-CT4PJ	▶ 4052899464858

Retrata

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.