

LEDDriving HLM EASY GEN 2 H7/H18



Ultra compact LED replacement for conventional H7/H18 high and low beam lamps

“Socket Design” – no adapters and caps needed



Easy plug & play installation

Allowing a high compatibility and an easy installation



Cool White color temperature

Better visibility thanks to daylight effect



LED high and low beams lamps with plug & play system: no adapters and caps needed.

With its socket-based solution, the OSRAM LEDDriving HLM EASY GEN 2 retrofits provide an ultra-compact LED replacement of conventional H7/H18 high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDDriving HLM EASY GEN 2 high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for motorcycles with the respective halogen lamp types.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Ficha técnica da família de produto

Dados técnicos

Descrição do produto	Dados elétricos			Dados fotométricos	
	Consumo máx. de potência	Tensão nominal	Potência nominal	Fluxo luminoso	Tolerância do fluxo luminoso
LEDDriving HL EASY GEN 2 ≙ H7/H18	16.0 W	12 V	16 W	2000 lm	±25 %

Descrição do produto	Atributos Físicos e Dimensões	Vida útil	Informações ambientais e regulamentares Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Diâmetro	Vida média Tc	Identificador primário do artigo	Número da declaração na base de dados SCIP
LEDDriving HL EASY GEN 2 ≙ H7/H18	20.0 mm	1000 hr	4062172420341	Em desenvolvimento

Download Data

Arquivo	
	User instruction GPRS_Instruções dos símbolos de segurança
	Brochures LEDiving Retrofits - Exchange overview (EN)

Instruções de segurança

Application advice:

For more detailed application information and graphics please see product datasheet and user manual.

Informações sobre aplicações

Para obter mais informações sobre aplicações e gráficos acesse a ficha técnica do produto.

Retratação

Sujeito a alteração sem prévio aviso. Sempre utilize a versão mais recente.