


## LEDDriving™ HL EASY XEN D1S



### Easy plug & play installation

Accurate mechanical compatibility – no adapters and/or caps needed



### Compact LED replacement for conventional high and low beam lamps

Same geometry as HID - allowing high compatibility with plenty of car models



### Cool White color temperature of 6,500 K

Better visibility thanks to daylight effect



### OSRAM's first Plug & Play off-road LED replacement for HID

With extra brightness the OSRAM LEDDriving HL EASY XEN ensures a compact LED replacement of conventional high and low beam lamps. These LED retrofit lamps are 12/24V compatible, come with a color temperature of 6,500 K and ensure a broader light distribution: more light allows to see better and therefore react sooner. The top OSRAM thermal management technology with integrated active cooling – a high speed fan - provides maximized heat dissipation for more powerful performances. Premium OSRAM quality and LED technology grant a long lifetime.

Please note: OSRAM LEDDriving HL EASY XEN change is recommended to be carried out by a professional.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Ficha técnica da família de produto

Dados técnicos

| Descrição do produto         | Dados Elétricos    |                |                  |                 | Dados fotométricos     |
|------------------------------|--------------------|----------------|------------------|-----------------|------------------------|
|                              | Entrada de energia | Tensão nominal | Potência nominal | Teste de tensão | Fluxo luminoso nominal |
| LEDDriving HL EASY XEN ≙ D1S | 40 W               | 12 V           | 40 W             | 13,2 V          | 5000 lm                |

| Descrição do produto         | Tolerância do fluxo luminoso | Physical Attributes & Dimensions | Espectativa de Vida | Informações Ambientais e Regulamentares Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                                       |
|------------------------------|------------------------------|----------------------------------|---------------------|---------------------------------------------------------------------------------------------------------------|---------------------------------------|
|                              |                              | Diâmetro                         | Lifespan Tc         | Identificador primário do artigo                                                                              | Lista de candidatos substância 1      |
| LEDDriving HL EASY XEN ≙ D1S | ±25 %                        | 13.8 mm                          | 5000 hr             | 4062172421447                                                                                                 | Nenhuma substância declarável contida |

| Descrição do produto         | Número da declaração no banco de dados SCIP |
|------------------------------|---------------------------------------------|
| LEDDriving HL EASY XEN ≙ D1S | Nenhuma substância declarável contida       |

Download Data

| Arquivo                                                                           |                                                               |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------|
|  | User instruction<br>GPRS_Instruções dos símbolos de segurança |

**Informações sobre aplicações**

Para obter mais informações sobre aplicações e gráficos acesse a ficha técnica do produto.

**Retratação**

Sujeito a alteração sem prévio aviso. Sempre utilize a versão mais recente.

