

LEDDriving HL EASY H8/H11/H16



Ultra compact LED replacement for conventional high and low beam lamps

"Socket Design" – no adapters and caps needed



Easy plug & play installation

Allowing a high compatibility and an easy installation



Cool White color temperature

Better visibility thanks to daylight effect



LED high and low beams lamps with plug & play system: no adapters and caps needed

With its socket-based solution, the OSRAM LEDDriving HL EASY GEN 2 retrofits provide an ultra-compact LED replacement of conventional high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDDriving HL EASY GEN 2 high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Ficha técnica da família de produto

Dados técnicos

Descrição do produto	Dados elétricos				Dados fotométricos
	Consumo máx. de potência	Tensão nominal	Potência nominal	Tensão de teste	Fluxo luminoso
LEDDriving HL EASY ≙ HB3/HIR1/H10/HB4/HIR2	26 W	12 V	26 W	13.2 V	2000 lm

Descrição do produto	Tolerância do fluxo luminoso	Atributos Físicos e Dimensões	Vida útil	Informações ambientais e regulamentares Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
		Diâmetro	Vida média Tc	Identificador primário do artigo	Número da declaração na base de dados SCIP
LEDDriving HL EASY ≙ HB3/HIR1/H10/HB4/HIR2	±25 %	14.8 mm	1000 hr	4062172426428	Em desenvolvimento

Ficha técnica da família de produto

Download Data

Arquivo



User instruction
GPRS_Instruções dos símbolos de segurança

Informações sobre aplicações

Para obter mais informações sobre aplicações e gráficos acesse a ficha técnica do produto.

Retratção

Sujeito a alteração sem prévio aviso. Sempre utilize a versão mais recente.

