

## Lightbar FX1000-CB SM GEN 2



**Single mount certified**  
For individual installation



**Up to 635 m long beam**  
Iluminação de campo  
próximo e distante  
melhorada



**Feixe combinado (Combo)**  
Designed for both: far-field  
and near-field illumination



**Classes de proteção IP e IK**  
Testado e validado em um  
laboratório de simulação  
ambiental certificado pela DIN  
em relação a influências  
externas extremas, como  
água, poeira, choques,  
impactos, calor, frio, vibrações  
permanentes e muito mais



### Increased brightness for far and near field illumination

Particularly when driving on rural and dirt roads, a greater range of visibility can play a key role in ensuring safety. The LEDriving Lightbar FX1000-CB SM GEN 2 provides additional, near and far field illumination on dark roads with up to 8.000 Lumen. Even in poor visibility conditions or at dusk, the 40 high-performance LEDs reach a light distance of up to 635 meters and daytime lighting conditions with a color temperature of 6000 Kelvin. The driving light impresses with its special reflector design and ensure not only a modern and appealing look but also reduces glare for more visibility on the road. It can be used as both a supplementary LED high beam headlight and a powerful working light. The light is fully ECE-compliant in both versions and therefore suitable for use on roads. Additionally, OSRAM has developed a specially designed mounting kit, compatible with all driving lights of the Functional series FX Gen 2 for individual mounting. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. Complete polarity protection both prevents damage from excess voltage and contributes to a longer lifespan. The LEDriving Lightbar FX1000-CB SM GEN 2 has been tested and validated with the IP-Protection Classes IP6K8 &

IP6K9K in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. Its variability gives the FX series a flexible range of uses. They can be attached to cars, trucks, agricultural machinery, commercial vehicles, construction vehicles, caravans, off-road vehicles and quads<sup>1)</sup>. OSRAM provides a 5-year guarantee<sup>2)</sup>. 1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed. 2) For precise conditions refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

Ficha técnica da família de produto

Dados técnicos

| Descrição do produto                                        | Dados Elétricos |                  |                 | Dados fotométricos     | Espectativa de Vida |
|-------------------------------------------------------------|-----------------|------------------|-----------------|------------------------|---------------------|
|                                                             | Tensão nominal  | Potência nominal | Teste de tensão | Fluxo luminoso nominal | Lifespan Tc         |
| Lightbar FX1000-CB SM GEN 2<br>LEDDL114-CB SM <sup>1)</sup> | 12/24 V         | 140 W            | 13,2 V          | 8000 lm                | > 5000 hr           |

| Descrição do produto                                        | Normas e Certificações   | Informações Ambientais e Regulamentares<br>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                         |                                                                                                         |
|-------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------|-------------------------|---------------------------------------------------------------------------------------------------------|
|                                                             | Número de referência ECE | Lista de candidatos substância 1                                                                                 | CAS No. da substância 1 | Instruções de uso seguro                                                                                |
| Lightbar FX1000-CB SM GEN 2<br>LEDDL114-CB SM <sup>1)</sup> | 50 + 50                  | Lead                                                                                                             | 7439-92-1               | A identificação da substância da Lista de Candidatos é suficiente para permitir o uso seguro do artigo. |

| Descrição do produto                                        | Número da declaração no banco de dados SCIP |
|-------------------------------------------------------------|---------------------------------------------|
| Lightbar FX1000-CB SM GEN 2<br>LEDDL114-CB SM <sup>1)</sup> | c2b80793-fe0b-4e19-b939-6a319f84b67b        |

<sup>1)</sup> Beam Pattern: Combo

Ficha técnica da família de produto

Download Data

| Arquivo                                                                             |                                                                                                            |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
|    | User instruction<br>LEDriving Lightbar FX1000-CB SM                                                        |
|    | User instruction<br>GPRS_Instruções dos símbolos de segurança                                              |
|    | Movie application<br>OSRAM LEDriving driving and working lights FX1000-CB SM (EN)                          |
|    | Movie application<br>LEDriving D and W Image Video Bringing light to life (EN)                             |
|    | Movie application<br>Working and Driving Lights Amarok Winter                                              |
|    | Movie application<br>LEDriving Driving and Working Lights Reference Video (EN)                             |
|    | Movie application<br>OSRAM LEDdriving and working lights Imagefilm (EN)                                    |
|    | Movie application<br>LEDriving driving & working lights in application (EN)                                |
|   | Movie application<br>OSRAM Quality Testing LEDriving working and driving lights (EN)                       |
|  | Video<br>Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)                   |
|  | Video<br>OSRAM LEDriving driving and working lights: The night doesn't stand a chance                      |
|  | Video<br>OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN) |
|  | Video<br>Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads  |
|  | ref_pim_ams_product360degreeimages<br>LEDriving Lightbar FX1000-CB SM LEDDL114-CB SM                       |

Instruções de segurança

Para obter informações detalhadas sobre a aplicação, consulte a ficha de dados do produto e o manual do usuário

Informação de legislação

1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.2) For precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

Informações sobre aplicações

Para obter mais informações sobre aplicações e gráficos acesse a ficha técnica do produto.

# Ficha técnica da família de produto

Retratação

Sujeito a alteração sem prévio aviso. Sempre utilize a versão mais recente.